




SCANNER DATA EDITING

Supported Model: Model ES201, ES301, MT1197M, MT1197MW, ES311 & MT7955TA

1. Download EzUtility from Arkscan.com, or from the CD that comes with the product package.
2. Right-click on EzUtility and tick 'Run this program as an administrator' in the pop-up menu. Complete the installation by double-clicking on the EzUtility.




3. After successful installation, please also right-click on the shortcut icon of **Ez Utility** on the desktop and tick 'Run this program as an administrator' in the pop-up menu.




4. Connect the scanner and the host with USB cable.
5. Scan [.C008\$]USB-HID below to switch to USB-HID interface.


8. Go to **Data Editing > Format Setting** and set parameters as below:




9. Go to **Data Editing > Block 1** and set parameters as below:




10. Go to **Data Editing** > **Block 2** and set parameters as below:



11. Go to **Data Editing > Block 3** and set parameters as below:



12. Go to **Data Editing > Code Type and Output** and set parameters as below:



In so doing, every 11-character Code39 will be defined into 3 blocks:


Block 1: the first 2 characters

Block 2: the characters from the 3rd to 10th position


Block 3: the last one character

And the final output will be Block 2 only.

13. Click the Up Arrow icon on the Toolbar to upload configurations to the scanner.



14. Now you are done!



15. The scanner will be able to output without prefix (“-B”) and suffix(“-”).



SCANNER DATA EDITING

Supported Model: Model ES201, ES301, MT1197M, MT1197MW, ES311 & MT7955TA

